

TEMCO® ULR.

转向导辊
产品预览.


—

2018 一月



Temco® ULR – 转向导辊

转向导辊示意图



预览

型号	辊		材料	涂层	联轴器						材料	L ₁ [mm]	v _{max} [m/min]
	D [mm]	L [mm]			d ₁ [mm]	l ₁ [mm]	d ₂ [mm]	l ₂ [mm]	d ₃ [mm]	l ₃ [mm]			
ULR34250-06**	34	250	CFRP				Ø29.6	25.0	M8	20.0	铝	275.0	750
ULR34250-07**	34	250	CFRP		M12	15.0	SW24	125.0			钢 黑化	390.0	750
ULR34250-08**	34	250	CFRP	防粘			Ø29.6	25.0	M8	20.0	铝	275.0	750
ULR34250-09**	34	250	CFRP	防粘	M12	15.0	SW24	125.0			钢 黑化	390.0	750
ULR34250-10**	34	250	CFRP		Ø18.0	45.0	Ø21.0	-1.5	M8	20.0	铝	293.5	750
ULR34250-11**	34	250	CFRP	防粘	Ø18.0	45.0	Ø21.0	-1.5	M8	20.0	铝	293.5	750
ULR34250-15	34	250	CFRP		Ø18.0	75.0	Ø21.0	-1.5	M8	20.0	铝	323.5	750
ULR34400-02**	34	400	CFRP		Ø18.0	45.0	Ø29.6	-1.5	M8	20.0	铝	443.5	600
ULR34400-E-03	34	400	CFRP				Ø30.0	15.0	M8	16.0	铝	415.0	400
ULR36200-E-00	36	200	ALU	阳极氧化								200.0	400
ULR36400-E-00	36	400	ALU	阳极氧化								400.0	400
ULR39130-E-01	39	130	ALU	硬质阳极氧化	Ø16.0	28.0	Ø22.0	135.0	M8	20.0	钢 黑化	293.0	400
ULR39220-E-01	39	220	ALU	硬质阳极氧化	Ø16.0	28.0	Ø22.0	81.0	M8	20.0	钢 黑化	329.0	400
ULR39320-E-01	39	320	ALU	硬质阳极氧化	Ø16.0	28.0	Ø22.0	31.0	M8	20.0	钢 黑化	379.0	400
ULR44200-02	44	200	CFRP		Ø20.0	50.0	Ø29.6	10.0	M8	20.0	铝	260.0	450
ULR44250-04	44	250	CFRP		M12	15.0	SW24	125.0			钢 黑化	390.0	550
ULR44250-11	44	250	CFRP		Ø18.0	45.0	Ø23.5	23.5	M8	20.0	铝	318.5	700
ULR44250-12	44	250	CFRP	防粘	Ø18.0	45.0	Ø23.5	23.5	M8	20.0	铝	318.5	700
ULR44300-02	44	300	CFRP		Ø20.0	50.0	Ø29.6	10.0	M8	20.0	铝	360.0	450
ULR44400-05	44	400	CFRP		Ø18.0	45.0	Ø29.6	-1.5	M8	20.0	铝	443.5	650
ULR44400-06	44	400	CFRP	防粘	Ø18.0	45.0	Ø29.6	-1.5	M8	20.0	铝	443.5	650
ULR44400-08	44	400	CFRP		Ø18	43.5	Ø29.6	23.5	M8	20.0	铝	443.5	450
ULR44400-09	44	400	CFRP	等离子喷涂	Ø18	43.5	Ø29.6	23.5	M8	20.0	铝	443.5	450
ULR60320-00**	60	320	CFRP		54.5	22.0			M12	22.0	铝	342.0	700
ULR60440-01	60	440	CFRP	防粘	Ø29.0	85.0					阳极氧化铝	540.0	700
ULR60440-02	60	440	ALU	硬质阳极氧化	Ø25.0	15.0	Ø35	120	M12	24.0	V2A	570.0	450
ULR60440-03	60	440	ALU	防粘	Ø25.0	15.0	Ø35	120	M12	24.0	V2A	570.0	450
ULR60440-04	60	440	ALU	硬质阳极氧化	Ø29.0	85.0					阳极氧化铝	540.0	450

** = 标准的

Saurer Technologies GmbH & Co. KG
Engineered Bearing Solutions

Fuldaer Str. 19

97762 Hammelburg

Germany / 德国

电话 +49 9732 87 0

传真 +49 9732 87 310

sales.temco@saurer.com

www.saurer.com